



SAFETY DATA SHEET

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SAS572 Brake & Air Line Sealant with PTFE

Container size 50ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Van-Line Ltd
Nina Works,
Gelderd Road,
Leeds
LS12 6NA

1.4. Emergency telephone number

Emergency telephone +44 (0) 113 213 4300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335 STOT SE 3 - H335 STOT SE 3 - H335

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

Precautionary statements	P261 Avoid breathing vapour/ spray.
	P264 Wash contaminated skin thoroughly after handling.
	P271 Use only outdoors or in a well-ventilated area.
	P272 Contaminated work clothing should not be allowed out of the workplace.
	P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
	P302+P352 IF ON SKIN: Wash with plenty of water.
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P312 Call a POISON CENTRE/doctor if you feel unwell.
	P321 Specific treatment (see medical advice on this label).
	P332+P313 If skin irritation occurs: Get medical advice/ attention.
	P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
	P337+P313 If eye irritation persists: Get medical advice/ attention.
	P362+P364 Take off contaminated clothing and wash it before reuse.
	P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.	
P501 Dispose of contents/ container in accordance with national regulations.	

Contains	Ethoxylated Bisphenol A Dimethacrylate, 2-hydroxypropyl methacrylate, α,α -dimethylbenzyl hydroperoxide, 1-Acetyl-2-phenylhydrazine
-----------------	---

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Ethoxylated Bisphenol A Dimethacrylate 30-60% CAS number: 41637-38-1
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335
Polyethylene Glycol 200 Dimethacrylate 10-30% CAS number: 26570-48-9
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319
2-hydroxypropyl methacrylate 5-10% CAS number: 923-26-2 EC number: 213-090-3
Classification Eye Irrit. 2 - H319 Skin Sens. 1 - H317

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

α,α-dimethylbenzyl hydroperoxide			1-5%
CAS number: 80-15-9	EC number: 201-254-7	REACH registration number: 01-2119475796-19-0000	
Classification			
Org. Perox. E - H242			
Acute Tox. 4 - H302			
Acute Tox. 4 - H312			
Acute Tox. 3 - H331			
Skin Corr. 1B - H314			
Eye Dam. 1 - H318			
STOT SE 3 - H335			
STOT RE 2 - H373			
Aquatic Chronic 2 - H411			
1-Acetyl-2-phenylhydrazine			<1%
CAS number: 114-83-0			
Classification			
Acute Tox. 3 - H301			
Skin Irrit. 2 - H315			
Eye Irrit. 2 - H319			
Skin Sens. 1 - H317			
STOT SE 3 - H335			
Titanium Dioxide			<1%
CAS number: 13463-67-7	EC number: 236-675-5	REACH registration number: 01-2119489379-17-0000	
Classification			
Not Classified			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Do not induce vomiting. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 10 minutes. Get medical attention if symptoms are severe or persist.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact	May cause sensitisation by skin contact.
Eye contact	Irritating. Conjunctivitis, irritation, tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide or dry powder.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Oxides of carbon. Oxides of nitrogen. Irritating gases or vapours.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Small Spillages: Wipe up with paper towels and place in container for disposal. Large Spillages: Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Use only in well-ventilated areas. Do not eat, drink or smoke when using this product. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store at temperatures between 8°C and 21°C. Keep only in the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Titanium Dioxide

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

WEL = Workplace Exposure Limit

8.2. Exposure controls

Eye/face protection Wear eye protection.

Hand protection Wear protective gloves made of the following material: Nitrile rubber.

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	White.
Odour	Mild.
Odour threshold	Not available.
pH	pH (concentrated solution): 3-6
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	> 100°C
Evaporation rate	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	Not available. <0.5 mm Hg @ °C
Vapour density	Not available.
Solubility(ies)	No information available.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	20000 cps
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Strong acids. Strong oxidants

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition products Irritating organic vapours

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Toxicological effects No information available.

Acute toxicity - oral

ATE oral (mg/kg) 27,886.19932074

Acute toxicity - dermal

ATE dermal (mg/kg) 109,890.10989011

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 299.7002997

Inhalation May cause respiratory system irritation.

Ingestion The product is considered to be a low hazard under normal conditions of use.

Skin contact May cause sensitisation by skin contact.

Eye contact Risk of serious damage to eyes.

SECTION 12: Ecological information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity**Ecotoxicity**

Toxicity Low

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No information available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

General information	Dispose of waste product or used containers in accordance with local regulations
Disposal methods	Dispose of waste product or used containers in accordance with local regulations
Waste class	08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the council of 18 December 2006 concerning the Registration, evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 14/10/2019

SAS572 BRAKE & AIR LINE SEALANT WITH PTFE

SDS number	5304
Hazard statements in full	H242 Heating may cause a fire. H301 Toxic if swallowed. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

WARRANTY: All products purchased from or supplied by Van-Line Ltd are subject to terms and conditions set out in the contract. Van-Line Ltd warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Van-Line Ltd is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Van-Line Ltd makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.