

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	ALU HITEMP
Registration number	-
Synonyms	None.
Product code	BDS001339AE
Issue date	22-December-2022
Version number	1.0
Revision date	22-December-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Anti Corrosion Products
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company name	CRC Industries UK Ltd.
Address	Wylds Road Castlefield Industrial Estate TA6 4DD Bridgwater Somerset United Kingdom
Telephone	+44 1278 727200
Fax	+44 1278 425644
E-mail	hse.uk@crcind.com
Website	www.crcind.com

Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1 9240 Zele Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	hse@crcind.com
Website	www.crcind.com

1.4. Emergency telephone number Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	---

Health hazards

Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 2-Methoxy-1-methylethyl acetate, acetone; propan-2-one; propanone, butan-1-ol; n-butanol, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, n-butyl acetate

Hazard pictograms

Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurized container: May burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements**Prevention**

P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing mist/vapours.
 P271 Use only outdoors or in a well-ventilated area.

Response Not assigned.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information EUH066 - Repeated exposure may cause skin dryness or cracking.

Dir. 2004/42/EC on the limitation of emissions of volatile organic compounds (VOC) of organic solvents in certain paints and varnishes and vehicle refinishing products: Cat.II B(e) VOC max 840 g/L < 675 g/L

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Dimethyl ether	25 - 50	115-10-6 204-065-8	-	603-019-00-8	#
Classification: Press. Gas;H280					
2-Methoxy-1-methylethyl acetate	5 - 15	108-65-6 203-603-9	01-2119475791-29	607-195-00-7	#
Classification: Flam. Liq. 3;H226, STOT SE 3;H336					
acetone; propan-2-one; propanone	5 - 10	67-64-1 200-662-2	01-2119471330-49	606-001-00-8	#
Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	1 - 5	EC919-857-5 919-857-5	01-2119463258-33	-	
Classification: Flam. Liq. 3;H226, STOT SE 3;H336, Asp. Tox. 1;H304					
n-butyl acetate	1 - 5	123-86-4 204-658-1	01-2119485493-29	607-025-00-1	#
Classification: Flam. Liq. 3;H226, STOT SE 3;H336					
xylene	1 - 5	1330-20-7 215-535-7	01-2119488216-32	601-022-00-9	#
Classification: Flam. Liq. 3;H226, Acute Tox. 4;H312, Acute Tox. 4;H332, Skin Irrit. 2;H315					

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
butan-1-ol; n-butanol	<2.5	71-36-3 200-751-6	01-2119484630-38	603-004-00-6	#

Classification: Flam. Liq. 3;H226, Acute Tox. 4;H302, Skin Irrit. 2;H315, Eye Dam. 1;H318, STOT SE 3;H335, STOT SE 3;H336

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media Alcohol resistant foam. Dry powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders Keep unnecessary personnel away. Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will sediment in water systems. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	STEL	548 mg/m ³
		100 ppm
	TWA	274 mg/m ³
acetone; propan-2-one; propanone (CAS 67-64-1)	STEL	50 ppm
		3620 mg/m ³
	TWA	1500 ppm
butan-1-ol; n-butanol (CAS 71-36-3)	STEL	1210 mg/m ³
		500 ppm
	TWA	154 mg/m ³
Dimethyl ether (CAS 115-10-6)	STEL	50 ppm
		958 mg/m ³
	TWA	500 ppm
n-butyl acetate (CAS 123-86-4)	STEL	766 mg/m ³
		400 ppm
	TWA	966 mg/m ³
xylene (CAS 1330-20-7)	STEL	200 ppm
		724 mg/m ³
	TWA	150 ppm
	STEL	441 mg/m ³
		100 ppm
	TWA	220 mg/m ³
		50 ppm

Biological limit values**UK. EH40 Biological Monitoring Guidance Values (BMGVs)**

Components	Value	Determinant	Specimen	Sampling Time
xylene (CAS 1330-20-7)	650 mmol/mol	Methyl hippuric acid	Creatinine in urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)**General population**

Components	Value	Assessment factor	Notes
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)			
Long-term, Local, Inhalation	33 mg/m ³	2	respiratory tract irritation
Long-term, Systemic, Dermal	320 mg/kg bw/day	16.8	Repeated dose toxicity
Long-term, Systemic, Inhalation	33 mg/m ³	2	respiratory tract irritation
Long-term, Systemic, Oral	36 mg/kg bw/day	28	Repeated dose toxicity
acetone; propan-2-one; propanone (CAS 67-64-1)			
Long-term, Systemic, Dermal	62 mg/kg bw/day	20	
Long-term, Systemic, Inhalation	200 mg/m ³	5	
Long-term, Systemic, Oral	62 mg/kg bw/day	2	
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)			
Long-term, Systemic, Dermal	300 mg/kg		
Long-term, Systemic, Inhalation	900 mg/m ³		
Long-term, Systemic, Oral	300 mg/kg		
n-butyl acetate (CAS 123-86-4)			
Long-term, Local, Inhalation	35.7 mg/m ³	12	irritation respiratory tract
Short-term, Local, Inhalation	300 mg/m ³		irritation respiratory tract
Short-term, Systemic, Dermal	6 mg/kg bw/day	100	Neurotoxicity
xylene (CAS 1330-20-7)			
Long-term, Local, Inhalation	65.3 mg/m ³	1.7	irritation respiratory tract
Long-term, Systemic, Dermal	125 mg/kg bw/day	1.7	Neurotoxicity
Short-term, Local, Inhalation	260 mg/m ³	1.7	Neurotoxicity

Workers

Components	Value	Assessment factor	Notes
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)			
Long-term, Systemic, Dermal	796 mg/kg bw/day	10.08	Repeated dose toxicity
Long-term, Systemic, Inhalation	275 mg/m ³	6	respiratory tract irritation
Short-term, Local, Inhalation	550 mg/m ³	3	respiratory tract irritation
acetone; propan-2-one; propanone (CAS 67-64-1)			
Long-term, Systemic, Dermal	186 mg/kg bw/day		
Long-term, Systemic, Inhalation	1210 mg/m ³		
Short-term, Local, Inhalation	2420 mg/m ³		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS EC919-857-5)			
Long-term, Systemic, Dermal	300 mg/kg		
Short-term, Systemic, Inhalation	1500 mg/m ³		
n-butyl acetate (CAS 123-86-4)			
Long-term, Local, Inhalation	300 mg/m ³	6	irritation respiratory tract
Long-term, Systemic, Dermal	7 mg/kg bw/day	25	Repeated dose toxicity
Short-term, Systemic, Dermal	11 mg/kg bw/day	50	Neurotoxicity
Short-term, Systemic, Inhalation	600 mg/m ³		irritation respiratory tract
xylene (CAS 1330-20-7)			
Long-term, Local, Inhalation	221 mg/m ³	1	irritation respiratory tract
Long-term, Systemic, Dermal	212 mg/kg bw/day	1	Neurotoxicity
Long-term, Systemic, Inhalation	221 mg/m ³	1	Neurotoxicity

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)			
Freshwater	0.635 mg/l	100	
Sediment (freshwater)	3.29 mg/kg		
Soil	0.29 mg/kg		
STP	100 mg/l	10	

acetone; propan-2-one; propanone (CAS 67-64-1)		
Freshwater	10.6 mg/l	50
Marine water	1.06 mg/l	500
Sediment (freshwater)	30.4 mg/kg	
Sediment (marine water)	3.04 mg/kg	
Soil	29.5 mg/kg	
STP	100 mg/l	10
n-butyl acetate (CAS 123-86-4)		
Freshwater	0.18 mg/l	100
Sediment (freshwater)	0.981 mg/kg	
Soil	0.09 mg/kg	
xylene (CAS 1330-20-7)		
Freshwater	0.327 mg/l	1
Sediment (freshwater)	12.46 mg/kg	1
Soil	2.31 mg/kg	1
STP	6.58 mg/l	1

Exposure guidelines

UK EH40 WEL: Skin designation

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
butan-1-ol; n-butanol (CAS 71-36-3)	Can be absorbed through the skin.
xylene (CAS 1330-20-7)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Suitable gloves can be recommended by the glove supplier. Nitrile gloves are recommended.

- Other

Not available.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid.

Form Aerosol.

Colour Grey.

Odour Characteristic odor.

Odour threshold Not available.

pH Not applicable.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point -35.0 °C (-31.0 °F) Closed cup

Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	0.6 % estimated
Explosive limit – upper (%)	12.8 % estimated
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.06 g/cm ³ at 20°C
Solubility(ies)	
Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not applicable
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	
VOC	492 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Nitrates.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Based on available data, the classification criteria are not met.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Product	Species	Test Results
ALU HITEMP		
Acute		
Dermal		
ATEmix		22022 mg/kg bw
Oral		
ATEmix		40000 mg/kg bw
Components	Species	Test Results
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		
Acute		
Dermal		
LD50	Rat	5100 mg/kg

Components	Species	Test Results
Inhalation		
LC50	Rat	30 mg/l/4h
Oral		
LD50	Rat	8532 mg/kg
acetone; propan-2-one; propanone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Rat	15800 mg/kg
Inhalation		
LC50	Rat	50.1 mg/l, 8 Hours
Oral		
LD50	Rat	5800 mg/kg
Dimethyl ether (CAS 115-10-6)		
Acute		
Inhalation		
LC50	Rat	308.5 mg/l, 4 Hours
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg
Oral		
LD50	Rat	> 5000 mg/kg
n-butyl acetate (CAS 123-86-4)		
Acute		
Dermal		
LD50	Rabbit	14122 mg/kg
Inhalation		
LC50	Rat	23.4 mg/l/4h
Oral		
LD50	Rat	14000 mg/kg
xylene (CAS 1330-20-7)		
Acute		
Dermal		
LD50	Rabbit	12126 mg/kg
Inhalation		
LC50	Rat	27124 mg/m ³
Oral		
LD50	Rat	3523 mg/kg
Skin corrosion/irritation	Based on available data, the classification criteria are not met.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	Not likely, due to the form of the product.	

Mixture versus substance information Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	Test Results
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	> 1000 mg/l, 72 h
Crustacea	EC50	Daphnia	> 400 mg/l, 48 h
Fish	LC50	Fish	> 100 - < 180 mg/l, 96 h
Dimethyl ether (CAS 115-10-6)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	4.4 mg/l
Fish	LC50	Fish	4.1 mg/l
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
<i>Acute</i>			
Other	LC50	Pseudokirchnerella subcapitata	> 1000 mg/l, 72 h
Aquatic			
<i>Acute</i>			
Fish	LC50	Oncorhynchus mykiss	> 1000 mg/l
n-butyl acetate (CAS 123-86-4)			
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	675 mg/l, 72 h
Crustacea	EC50	Daphnia	73 mg/l, 24 h
Fish	LC50	Fish	62 mg/l, 96 h

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

acetone; propan-2-one; propanone	-0.24
butan-1-ol; n-butanol	0.88
Dimethyl ether	0.1
n-butyl acetate	1.78

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.
GWP: 1

Substance Global Warming Potential per (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases, as amended

Dimethyl ether (CAS 115-10-6)	1
-------------------------------	---

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Hazard No. (ADR)	Not assigned.
Tunnel restriction code	D
ADR/RID - Classification code:	5F
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	No.
ERG Code	10L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not assigned.
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

acetone; propan-2-one; propanone (CAS 67-64-1)
xylene (CAS 1330-20-7)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

acetone; propan-2-one; propanone (CAS 67-64-1)
butan-1-ol; n-butanol (CAS 71-36-3)
Dimethyl ether (CAS 115-10-6)
xylene (CAS 1330-20-7)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

acetone; propan-2-one; propanone (CAS 67-64-1)
butan-1-ol; n-butanol (CAS 71-36-3)
Dimethyl ether (CAS 115-10-6)
n-butyl acetate (CAS 123-86-4)
xylene (CAS 1330-20-7)

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.