REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016

Product code: 00156-0029



SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision No: 2.2

1.1. Product identifier

TIP TOP CEMENT SVS VULC

Art.-No.

 $505\ 0196,\ 505\ 4037,\ 505\ 4051,\ 505\ 9010,\ 505\ 9018,\ 505\ 9025,\ 505\ 9032,\ 505\ 9035,\ 505\ 9036,\ 505$ $9037,\ 505\ 9050,\ 505\ 9056,\ 505\ 9128,\ 505\ 9142,\ 505\ 9159,\ 505\ 9197,\ 505\ 9245,\ 505\ 9252,\ 506\ 0000,\ 506\ 0007,\ 506\ 0021,\ 506\ 0045,\ 506\ 0048,\ 506\ 0100,\ 506\ 0103,\ 506\ 0117,\ 506\ 0193,\ 506\ 0203,\ 506$ $0306,\ 506\ 0375,\ 506\ 0519,\ 506\ 0605,\ 506\ 0900,\ 506\ 0911,\ 506\ 1500,\ 506\ 4003,\ 506\ 4004,\ 506\ 4005,\ 506\ 4027,\ 506\ 4041,\ 506\ 4190,\ 506\ 4191,\ 506\ 4195,\ 506\ 4199,\ 506\ 4200,\ 506\ 4201,\ 506$ $4209,\ 506\ 4254,\ 506\ 4302,\ 506\ 4371,\ 506\ 4515,\ 506\ 4601,\ 506\ 8100,\ 506\ 9015,\ 506\ 9022,\ 506\ 9030,\ 506\ 9053,\ 506\ 9060,\ 506\ 9101,\ 506\ 9118,\ 506\ 9120,\ 506\ 9132,\ 506\ 9133,\ 506\ 9148,\ 506\ 9149,\ 506$ $9150,\ 506\ 9163,\ 506\ 9170,\ 506\ 9190,\ 506\ 9500,\ 506\ 9520,\ 506\ 9521,\ 506\ 9534,\ 506\ 9637,\ 507\ 0011,\ 507\ 0310,\ 507\ 0602,\ 507\ 9892,\ 546\ 2313,\ 552\ 3199,\ 552\ 4196,\ 596\ 4354,\ 5042,\ 5042,\ 5042-10,\ 5952,\ 5952-10,\ 5098-10,\ 5098,\ 5096$

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

adhesive

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 63
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 0

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture according to 1272/2008/EC

Hazard categories:

Flammable liquid: Flam. Liq. 2 Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour. Causes serious eye irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H315 Causes skin irritation.

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016 Revision No: 2,2

Product code: 00156-0029



H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P273 Avoid release to the environment.

P501 Dispose of contents/container to waste treatment facility in accordance with local and

national regulations.

2.3. Other hazards

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation solved in petroleum spirit

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Naphtha (petroleum) (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane)			< 95 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
5459-93-8	N-Cyclohexyl-N-ethylamine			< 2,5 %
	226-733-8		01-2119949285-29	
	Flam. Liq. 3, Acute Tox. 3, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Aquatic Chronic 3; H226 H311 H331 H302 H314 H412			

Full text of H and EUH statements: see section 16.

Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphta (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.

Seek medical treatment immediately.

After contact with skin

Wash off immediately with soap and plenty of water.

Treat subsequently with skin cream.

Consult a doctor if skin irritation persists.

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016 Product code: 00156-0029 Revision No: 2,2



After contact with eyes

If eye irritation persists, consult a specialist.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

After ingestion

Do not induce vomiting.

Attention. Beware, danger of aspiration.

Summon a doctor immediately.

Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Attention. Beware, danger of aspiration.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam, carbon dioxide (CO2), dry chemical, water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Vapours are heavier than air and spread along ground.

The vapour/air mixture is explosive, even in empty, uncleaned receptacles.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Use personal protective clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed.

Revision No: 2.2

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016

Product code: 00156-0029



Vapours are heavier than air and spread along ground.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from heat and sources of ignition.

Do not smoke.

Take precautionary measures against static discharges.

Use only explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Pay attention to anti-explosion rules.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Treat subsequently with skin cream.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Hand protection

Protective gloves resistant to chemicals made of nitrile, minimum coat thickness 0.4 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove < Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Solvent-resistant apron (EN 467).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Colourless

Odour: Hydrocarbon-like

Changes in the physical state

Melting point: < - 50 °C *)

Print date: 13.04.2016 GB - EN Page 4 of 9

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016 Revision No: 2.2

Product code: 00156-0029



*)

> 60 °C Initial boiling point and boiling range:

Flash point: - 25 °C **DIN EN ISO 3679**

Explosive properties The product is considered non-explosive; nevertheless explosive vapour/air

mixture can be generated.

Lower explosion limits: *) 0,8 vol. % 8.0 vol. % *) Upper explosion limits: 260 °C Ignition temperature: *) Vapour pressure: 190 hPa

(at 20 °C)

Density (at 20 °C): 0,72 g/cm³ Water solubility: Immiscible

(at 20 °C)

Viscosity / dynamic: 2900 - 3500 mPa·s Viscosity / kinematic: $> 20.5 \text{ mm}^2/\text{s}$

(at 40 °C)

Flow time: > 30 s3 DIN EN ISO 2431

(at 23 °C)

Solvent content: > 90 %

9.2. Other information

*) Naphtha (petroleum)

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx).

An inappropriate handling, for instance major amounts of product combined with strong heat and

nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Naphtha (petroleum)

LD50/oral/rat: > 2000 mg/kg

LD50/dermal/rabbit: > 2000 mg/kg

LC50/inhalation/rat: No data available.

Irritation and corrosivity

Causes serious eye irritation.

Causes skin irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Print date: 13.04.2016 GB - EN Page 5 of 9

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016 Product code: 00156-0029 Revision No: 2,2

REMA TOP

May cause drowsiness or dizziness. (Naphtha (petroleum) (Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 3% n-hexane))

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

A longer or repeated contact my lead to irritation of eyes and mucous membranes.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Naphtha (petroleum)

LC50/EC50/EC50: 1 - 10 mg/l

N-Cyclohexyl-N-ethylamine

EC50/Daphnia magna/48 h = 10 - 100 mg/l

ErC50/Desmodesmus subspicatus/72 h = 10 - 100 mg/l

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080409

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016 Revision No: 2,2

Product code: 00156-0029



Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be

taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Limited quantity: 1 L / 30 kg

Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

HAZCHEM: 3YE

Inland waterways transport (ADN)

14.1. UN number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Limited quantity: 1 L / 30 kg

Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (Naphtha (Petroleum))

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



 $\begin{tabular}{llll} Marine pollutant: & Yes \\ Limited quantity: & 1 L / 30 kg \\ Excepted quantity: & E2 \\ EmS: & F-E, S-D \\ \end{tabular}$

Air transport (ICAO)

14.1. UN number: UN 3295

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016 Revision No: 2,2

Product code: 00156-0029



14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): < 95 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

REMATIP TOP AG

TIP TOP CEMENT SVS VULC

Revision date: 13.04.2016 Revision No: 2.2

Product code: 00156-0029



GHS = Globally Harmonized System of Classification and Labelling of Chemicals REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

REMATIP TOP AG

Revision date: 27.01.2015 Revision No: 2,01

REMA TIP TOP REPAIR PATCH

00156-0361



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

REMATIP TOP REPAIR PATCH

Art.-No.

EC-SDS applicable for following products:

Tube-Patch, Tyre Repair Patches of series RAD100, RAD200, RAD500, PN, FRU, MTC, Radial-E,

Diagonal-E, UP, M-RCV and M-RCF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Rubberpatch for repair of radial and diagonal tyres.

1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG
Street: Gruber Strasse 63
Place: D-85586 Poing
Telephone +49 (0) 8121 / 707 - 0
Verantwortlich für das Sicherheitsdatenblatt: sds@gbk-ingelheim.de

1.4. Emergency telephone INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

number: England and Wales: NHS Direct - 0845 4647; Scotland: NHS 24 - 08454 24 24

24

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This mixture is not classified as hazardous according to Directive 1999/45/EC.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

2.2. Label elements

Additional advice on labelling

As an article the product does not need to be labelled in accordance with EC-directives or respective national laws.

2.3. Other hazards

Not known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Vulcanized product of rubber, sulphur and other additives with tyre cord (fabric).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No hazards which require special first aid measures.

After inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.

After contact with skin

Wash with water and soap as a precaution.

After ingestion

Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

May cause sensitization of susceptible persons by skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

REMATIP TOP AG

Revision date: 27.01.2015

Revision No: 2,01



REMA TIP TOP REPAIR PATCH

00156-0361

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Any extinguishing means and measures are acceptable. Fire-extinguishing activities according to surrounding.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:

Carbon monoxide, carbon dioxide and sulphur oxides.

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.

Protective suit.

Additional information

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

In case of vapour formation use respirator.

Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

Take up mechanically and collect in suitable container for disposal.

Where possible recycling is preferred to disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).

Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Do not breath vapours that may be evolved during processing.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition.

The product is flammable but not readily ignited.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a dry, cool place.

Advice on storage compatibility

Incompatible with:

Nitrous acid and other nitrosating agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Rubberpatch for repair of radial and diagonal tyres.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

REMATIP TOP AG

Revision date: 27.01.2015

Revision No: 2,01



REMA TIP TOP REPAIR PATCH

00156-0361

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, minimum coat thickness 0.6 mm, permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de. Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of respirable dust and/or fumes, use a self-contained breathing apparatus.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Solid
Colour: Black
Odour: Rubbery

Flash point: n.a. Lower explosion limits: n.a.

Upper explosion limits:

Density: n.d.
Water solubility: insoluble
(at 20 °C)

Ignition temperature: n.a.

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts with:

Nitrous acid and other nitrosating agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

10.5. Incompatible materials

Nitrous acid and other nitrosating agents.

10.6. Hazardous decomposition products

Carbon monoxide, carbon dioxide, sulphur oxides.

An inappropriate handling, for instance major amounts of product combined with strong heat and nitrosating agents, renders possible a cleavage of nitrosamines in traces.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

REMATIP TOP AG

Revision date: 27.01.2015

REMATIP TOP REPAIR PATCH

00156-0361



Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Revision No: 2.01

Further information

May cause sensitization of susceptible persons by skin contact.

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known. Product contains low quantities of cancerogenic and mutagenic components. Nevertheless it is not hazardous to health if inhaled, swallowed or in case of contact with skin under this form.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

Because of the low solubility a toxicity to aquatic organisms is not to be expected.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

No data available.

Further information

Do not flush into surface water or sanitary sewer system.

Ecological injuries are not known or expected under normal use.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Where possible recycling is preferred to disposal.

Can be incinerated, when in compliance with local regulations.

Waste disposal number of waste from residues/unused products

080410

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and

sealants other than those mentioned in 08 04 09

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

REMATIP TOP AG

Revision date: 27.01.2015

Revision No: 2,01



REMA TIP TOP REPAIR PATCH

00156-0361

SECTION 14: Transport information

Land transport (ADR/RID); Marine transport (IMDG); Air transport (ICAO); Inland waterways transport (ADN)

14.1. UN number:

No hazardous material as defined by the transport regulations.

14.2. UN proper shipping name:

No hazardous material as defined by the transport regulations.

14.3. Transport hazard class(es):

No hazardous material as defined by the transport regulations.

14.4. Packing group:

No hazardous material as defined by the transport regulations.

14.5. Environmental hazards

No hazardous material as defined by the transport regulations.

14.6. Special precautions for user

No hazardous material as defined by the transport regulations.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No hazardous material as defined by the transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

1999/13/EC (VOC):

0%

National regulatory information

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

REMATIP TOP AG

00156-0361

Revision date: 27.01.2015

Revision No: 2,01



REMA TIP TOP REPAIR PATCH

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)