

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 16

SDS No.: 153641 V005.0

Revision: 21.11.2016

printing date: 17.10.2017

Replaces version from: 27.01.2015

# LOCTITE 268

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE 268

#### **Contains:**

A mixture of: N,N'-Ethane-1,2-diylbis(decanamide); 12-Hydroxy-N-[2-[1-oxydecyl)amino]ethyl]octadecanamide; N,N'-Ethane-1,2-diylbis(1

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Threadlocker

# 1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-products a fety. uk@uk.henkel.com

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Classification (CLP):

	Category 1
H317 May cause an allergic skin reaction.	
	Category 3
H412 Harmful to aquatic life with long lasting effects.	

#### 2.2. Label elements

## Label elements (CLP):



Signal word: Warning

MSDS-No.: 153641 LOCTITE 268 Page 2 of 16

V005.0

Hazard statement:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement: Prevention	P280 Wear protective gloves. P273 Avoid release to the environment.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

#### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

# **General chemical description:** Threadlocker Stick

MSDS-No.: 153641 LOCTITE 268 Page 3 of 16

V005.0

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
A mixture of: N,N'-Ethane-1,2-diylbis(decanamide); 12-Hydroxy-N-[2-[1-oxydecyl)amino]ethyl]octadecanamide; N,N'-Ethane-1,2-diylbis(1	430-050-2	10-< 20 %	Skin Sens. 1 H317 Aquatic Chronic 2 H411
Cumene hydroperoxide 80-15-9	201-254-7	0,1-< 1 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
N,N-Diethyl-p-toluidine 613-48-9	210-345-0	0,1-< 1 %	Acute Tox. 3; Oral H301 Acute Tox. 3; Dermal H311 Acute Tox. 3; Inhalation H331 STOT RE 2 H373 Aquatic Chronic 3 H412
1-Methyl-2-pyrrolidone 872-50-4	212-828-1 01-2119472430-46	0,1-< 1 %	Repr. 1B H360D Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 ==== EU. REACH Candidate List of Substances of Very High Concern for Authorization (SVHC)
N,N-dimethyl-o-toluidine 609-72-3	210-199-8	0,1-< 1 %	Acute Tox. 3; Inhalation H331 Acute Tox. 3; Dermal H311 Acute Tox. 3; Oral H301 STOT RE 2 H373 Aquatic Chronic 3 H412
1,4-Naphthalenedione 130-15-4	204-977-6	100- < 250 PPM	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10

MSDS-No.: 153641 LOCTITE 268 Page 4 of 16

V005.0

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

Fine water spray

# Extinguishing media which must not be used for safety reasons:

None known

# 5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

# 5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

## Additional information:

In case of fire, keep containers cool with water spray.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

MSDS-No.: 153641 LOCTITE 268 Page 5 of 16

V005.0

#### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

See advice in section 8

#### Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

# 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction. Store in a cool, well-ventilated place.

#### 7.3. Specific end use(s)

Threadlocker

MSDS-No.: 153641 LOCTITE 268 Page 6 of 16

V005.0

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

# **Occupational Exposure Limits**

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silicon dioxide 112945-52-5 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	20	80	Short Term Exposure Limit (STEL):		EH40 WEL
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	10	40	Time Weighted Average (TWA):		EH40 WEL
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	10	40	Time Weighted Average (TWA):	Indicative	ECTLV
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]	20	80	Short Term Exposure Limit (STEL):	Indicative	ECTLV
1-Methyl-2-pyrrolidone 872-50-4 [N-METHYL-2-PYRROLIDONE]			Skin designation:	Can be absorbed through the skin.	ECTLV
Cumene 98-82-8 [CUMENE]	50	250	Short Term Exposure Limit (STEL):		EH40 WEL
Cumene 98-82-8 [CUMENE]			Skin designation:	Can be absorbed through the skin.	EH40 WEL
Cumene 98-82-8 [CUMENE]	25	125	Time Weighted Average (TWA):		EH40 WEL
Cumene 98-82-8 [CUMENE]	50	250	Short Term Exposure Limit (STEL):	Indicative	ECTLV
Cumene 98-82-8 [CUMENE]	20	100	Time Weighted Average (TWA):	Indicative	ECTLV

# Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silicon dioxide		6	Time Weighted Average		IR_OEL
112945-52-5			(TWA):		
[SILICA, AMORPHOUS, TOTAL					
INHALABLE DUST]					
Silicon dioxide		2,4	Time Weighted Average		IR_OEL
112945-52-5			(TWA):		
[SILICA, AMORPHOUS, RESPIRABLE					

MSDS-No.: 153641 LOCTITE 268 Page 7 of 16

V005.0

DUSTI	1	1			1
Ethene, homopolymer		4	Time Weighted Average		IR OEL
9002-88-4		'	(TWA):		IN_OLL
[DUSTS, NON-SPECIFIC, RESPIRABLE]					
Ethene, homopolymer		10	Time Weighted Average		IR_OEL
9002-88-4			(TWA):		
[DUSTS, NON-SPECIFIC, TOTAL					
INHALABLE]					
1-Methyl-2-pyrrolidone	10	40	Time Weighted Average	Indicative OELV	IR_OEL
872-50-4			(TWA):		
[1-METHYL-2-PYRROLIDONE]					ID OFF
1-Methyl-2-pyrrolidone 872-50-4			Skin designation:	Can be absorbed through the skin.	IR_OEL
[1-METHYL-2-PYRROLIDONE]				SKIII.	
1-Methyl-2-pyrrolidone	20	80	Short Term Exposure	Indicative OELV	IR OEL
872-50-4	20	80	Limit (STEL):	indicative OEL v	IK_OEL
[1-METHYL-2-PYRROLIDONE]			Ellint (STEE).		
1-Methyl-2-pyrrolidone	10	40	Time Weighted Average	Indicative	ECTLV
872-50-4			(TWA):		
[N-METHYL-2-PYRROLIDONE]					
1-Methyl-2-pyrrolidone	20	80	Short Term Exposure	Indicative	ECTLV
872-50-4			Limit (STEL):		
[N-METHYL-2-PYRROLIDONE]					
1-Methyl-2-pyrrolidone			Skin designation:	Can be absorbed through the	ECTLV
872-50-4				skin.	
[N-METHYL-2-PYRROLIDONE]		100			
Cumene 98-82-8	20	100	Time Weighted Average	Indicative OELV	IR_OEL
[ISOPROPYL BENZENE]			(TWA):		
Cumene	50	250	Short Term Exposure	Indicative OELV	IR OEL
98-82-8	30	230	Limit (STEL):	indicative OEL v	IK_OEL
[ISOPROPYL BENZENE]			Ellint (STEE).		
Cumene			Skin designation:	Can be absorbed through the	IR OEL
98-82-8				skin.	
[ISOPROPYL BENZENE]					
Cumene	50	250	Short Term Exposure	Indicative	ECTLV
98-82-8			Limit (STEL):		
[CUMENE]					
Cumene	20	100	Time Weighted Average	Indicative	ECTLV
98-82-8			(TWA):		
[CUMENE]					

MSDS-No.: 153641 LOCTITE 268 Page 8 of 16

V005.0

# $\label{eq:predicted} \textbf{Predicted No-Effect Concentration (PNEC):}$

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (freshwater)					0,0031 mg/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)					0,00031 mg/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (intermittent releases)					0,031 mg/L	
.alpha.,alphaDimethylbenzyl hydroperoxide 80-15-9	Sewage treatment plant					0,35 mg/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (freshwater)				0,023 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)				0,0023 mg/kg		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	soil				0,0029 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	aqua (freshwater)					0,25 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	aqua (marine water)					0,025 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	aqua (intermittent releases)					5 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	sediment (freshwater)				0,805 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	soil				0,138 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	sewage treatment plant (STP)					10 mg/L	
1-Methyl-2-pyrrolidone 872-50-4	oral				0,00167 mg/kg		
1-Methyl-2-pyrrolidone 872-50-4	sediment (marine water)				0,0805 mg/kg		

MSDS-No.: 153641 LOCTITE 268 Page 9 of 16

V005.0

#### **Derived No-Effect Level (DNEL):**

Name on list	Application	Route of	Health Effect	Exposure	Value	Remarks
	Area	Exposure		Time		
.alpha.,.alphaDimethylbenzyl	Workers	inhalation	Long term		6 mg/m3	
hydroperoxide			exposure -			
80-15-9			systemic effects			
1-Methyl-2-pyrrolidone	Workers	dermal	Acute/short term		208 mg/kg bw/day	
872-50-4			exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	Workers	Inhalation	Acute/short term		80 mg/m3	
872-50-4			exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	Workers	dermal	Long term		19,8 mg/kg bw/day	
872-50-4			exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	Workers	Inhalation	Long term		40 mg/m3	
872-50-4			exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	General	dermal	Acute/short term		125 mg/kg bw/day	
872-50-4	population		exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	General	Inhalation	Acute/short term		80 mg/m3	
872-50-4	population		exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	General	oral	Acute/short term		26 mg/kg bw/day	
872-50-4	population		exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	General	dermal	Long term		11,9 mg/kg bw/day	
872-50-4	population		exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	General	Inhalation	Long term		12,5 mg/m3	
872-50-4	population		exposure -			
			systemic effects			
1-Methyl-2-pyrrolidone	General	oral	Long term		6,3 mg/kg bw/day	
872-50-4	population		exposure -			
			systemic effects			

# **Biological Exposure Indices:**

None

# 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

# Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

MSDS-No.: 153641 LOCTITE 268 Page 10 of 16

V005.0

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Appearance solid material

wax red

Odor mild

Odour threshold No data available / Not applicable

pH Not applicable Initial boiling point  $> 149 \,^{\circ}\text{C} \, (> 300.2 \,^{\circ}\text{F})$  Flash point Not applicable

Decomposition temperature No data available / Not applicable

Vapour pressure < 6,67 mbar

(20 °C (68 °F))

Density 1,07 g/cm3

()

Bulk density
No data available / Not applicable
Viscosity
No data available / Not applicable
Viscosity (kinematic)
No data available / Not applicable
Explosive properties
No data available / Not applicable

Solubility (qualitative) Slight

(Solvent: Water)

Solubility (qualitative) Not applicable

(Solvent: Acetone)

Solidification temperature No data available / Not applicable No data available / Not applicable Melting point Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable Vapor density Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Strong oxidizing agents.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

MSDS-No.: 153641 LOCTITE 268 Page 11 of 16

V005.0

#### 10.4. Conditions to avoid

No decomposition if used according to specifications.

#### 10.5. Incompatible materials

See section reactivity.

#### 10.6. Hazardous decomposition products

carbon oxides.

# **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### Inhalative toxicity:

May cause irritation to respiratory system.

#### Skin irritation:

Prolonged or repeated contact may cause skin irritation.

#### Eye irritation:

Prolonged or repeated contact may cause eye irritation.

#### Sensitizing

May cause an allergic skin reaction.

## Acute oral toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	not specified
80-15-9						
1-Methyl-2-pyrrolidone	LD50	4.150 mg/kg	oral		rat	OECD Guideline 401 (Acute
872-50-4						Oral Toxicity)
1,4-Naphthalenedione	LD50	190 mg/kg	oral		rat	not specified
130-15-4						_

### Acute inhalative toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
1-Methyl-2-pyrrolidone 872-50-4	LC50	> 5,1 mg/l	aerosol	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

## Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Cumene hydroperoxide	LD50	1.200 - 1.520	dermal			not specified
80-15-9		mg/kg				
1-Methyl-2-pyrrolidone	LD50	> 5.000 mg/kg	dermal		rat	OECD Guideline 402 (Acute
872-50-4						Dermal Toxicity)

# Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
1-Methyl-2-pyrrolidone 872-50-4	irritating	24 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1-Methyl-2-pyrrolidone 872-50-4	moderately irritating		human	not specified

MSDS-No.: 153641 LOCTITE 268 Page 12 of 16

V005.0

# Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
1-Methyl-2-pyrrolidone	irritating		rabbit	OECD Guideline 405 (Acute
872-50-4	-			Eye Irritation / Corrosion)

# Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
1-Methyl-2-pyrrolidone 872-50-4	not sensitising	Mouse local lymphnod	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
		e assay (LLNA)		

#### Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified
1-Methyl-2-pyrrolidone 872-50-4	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1-Methyl-2-pyrrolidone 872-50-4	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
	negative	oral: gavage		hamster, Chinese	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)

## Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
1-Methyl-2-pyrrolidone 872-50-4	NOAEL=0,5 mg/l	inhalation	90 days6 hrs/day, 5 days/wk	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

# **SECTION 12: Ecological information**

#### General ecological information:

In the cured state contribution of this product to Environmental Hazards is insignificant in comparison to articles in which it is used.

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

MSDS-No.: 153641 LOCTITE 268 Page 13 of 16

V005.0

#### 12.1. Toxicity

#### **Ecotoxicity:**

Do not empty into drains / surface water / ground water.

Harmful to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline
80-13-9						203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
80-15-9						202 (Daphnia sp.
						Acute Immobilisation
						Test)
Cumene hydroperoxide	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
80-15-9						201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide	EC10	70 mg/l	Bacteria	30 min		not specified
80-15-9	] .					
1-Methyl-2-pyrrolidone 872-50-4	LC50	4.000 mg/l	Fish	96 h	Leuciscus idus	DIN 38412-15
1-Methyl-2-pyrrolidone	EC50	4.897 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
872-50-4						202 (Daphnia sp. Acute
						Immobilisation
						Test)
1-Methyl-2-pyrrolidone 872-50-4	EC50	> 500 mg/l	Algae	72 h	Scenedesmus subspicatus (new name: Desmodesmus	DIN 38412-09
872-30-4					subspicatus)	
1-Methyl-2-pyrrolidone	NOEC	12,5 mg/l	chronic	21 d	Daphnia magna	OECD 211
872-50-4			Daphnia			(Daphnia magna,
1,4-Naphthalenedione	EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	Reproduction Test) OECD Guideline
130-15-4		-,1 <b>g</b> 1	8	, 211		201 (Alga, Growth
						Inhibition Test)

# 12.2. Persistence and degradability

# Persistence and Biodegradability:

The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1-Methyl-2-pyrrolidone 872-50-4	inherently biodegradable	aerobic	> 90 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
	readily biodegradable	aerobic	92 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F

# 12.3. Bioaccumulative potential / 12.4. Mobility in soil

#### **Mobility:**

Cured adhesives are immobile.

## Bioaccumulative potential:

No data available.

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

MSDS-No.: 153641 LOCTITE 268 Page 14 of 16

V005.0

Cumene hydroperoxide 80-15-9 Cumene hydroperoxide 80-15-9	2,16	9,1	calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test) not specified
1-Methyl-2-pyrrolidone 872-50-4	-0,46			25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	1,71				not specified

#### 12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
1-Methyl-2-pyrrolidone	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
872-50-4	Bioaccumulative (vPvB) criteria.

#### 12.6. Other adverse effects

No data available.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

#### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

MSDS-No.: 153641 LOCTITE 268 Page 15 of 16

V005.0

# **SECTION 14: Transport information**

#### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

# 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

< 3 %

VOC content (2010/75/EC)

# 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

MSDS-No.: 153641 LOCTITE 268 Page 16 of 16

V005.0

# **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H360D May damage the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.