

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

| 1.1. Product identifier Trade name or designation of the mixture | Hylomar Exhaust Repair Putty ERP5 | |
|--|-------------------------------------|--|
| Registration number | - | |
| UFI: | GS00-E0W3-K00F-C067 | |
| Synonyms | None. | |
| SDS number | 36 | |
| Issue date | 21-April-2017 | |
| Version number | 02 | |
| Revision date | 15-March-2022 | |
| Supersedes date | 21-April-2017 | |
| 1.2. Relevant identified uses of the substance or mixture and uses advised against | | |
| Identified uses | Exhaust putty. | |
| Uses advised against | None known. | |
| 1.3. Details of the supplier of the safety data sheet | | |
| Manufacturer: | Hylomar Ltd. | |
| Address: | Hylo House, Cale Lane, New Springs, | |
| | Wigan, Greater Manchester, | |
| | UK, WN2 1JT | |
| Telephone number: | +44(0)1942 617000 | |
| E-mail address: | info@hylomar.co.uk | |
| Contact person: | Technical Department | |
| 1.4. Emergency telephone number | +1-760-476-3961 (US) | |
| | Access code: 333544 | |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

| Health hazards | | |
|-----------------------------------|------------|--|
| Skin corrosion/irritation | Category 2 | H315 - Causes skin irritation. |
| Serious eye damage/eye irritation | Category 2 | H319 - Causes serious eye irritation. |

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms



| Signal word | Warning |
|--------------------------|--|
| Hazard statements | |
| H315 H319 | Causes skin irritation. Causes serious eye irritation. |
| Precautionary statements | |
| Prevention | |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| Response | |
| P302 + P352 | IF ON SKIN: Wash with plenty of soap and water. |

| P305 + P351 + P338 P337 + P313 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
|---------------------------------------|--|
| Storage | Store away from incompatible materials. |
| Disposal | |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Supplemental information on the label | None. |
| 2.3. Other hazards | This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. |

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

| General information | | | |
|---|---|--|--|
| Chemical name | % CAS-No. / EC No. REACH Registration No. Index No. Notes | | |
| Silicic acid, sodium salt | 30 - 50 1344-09-8 01-2119448725-31-XXXX - 215-687-4 | | |
| Classif | fication: Skin Irrit. 2;H315, Eye Irrit. 2;H319, STOT SE 3;H335 | | |
| Composition comments | All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16. | | |
| | Contains: Silicic acid, sodium salt. The classification as a specific target organ toxicant category 3; H335 (May cause respiratory irritation) applies to the substance in powder form. | | |
| SECTION 4: First aid meas | sures | | |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. | | |
| 4.1. Description of first aid meas | sures | | |
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. | | |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. If skin irritation occurs: Get medical advice/attention. | | |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. | | |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. | | |
| 4.2. Most important symptoms and effects, both acute and delayed | Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. | | |
| 4.3. Indication of any immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. | | |
| SECTION 5: Firefighting m | neasures | | |
| General fire hazards | Will burn if involved in a fire. | | |
| 5.1. Extinguishing media Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). | | |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. | | |
| 5.2. Special hazards arising from the substance or mixture | During fire, gases hazardous to health may be formed. | | |
| 5.3. Advice for firefighters Special protective equipment for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. | | |
| Special fire fighting procedures | Move containers from fire area if you can do so without risk. | | |
| | | | |

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency
personnelWear appropriate protective equipment and clothing during clean-up. Avoid breathing
mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate
protective clothing.

| For emergency responders | Keep unnecessary personnel away. Wear protective clothing as described in Section 8 of this safety data sheet. |
|---|--|
| 6.2. Environmental precautions | Prevent further leakage or spillage if safe to do so. Do not discharge into drains, water courses or onto the ground. |
| 6.3. Methods and material for containment and cleaning up | Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste for proper disposal. Following product recovery, flush area with water. |
| | Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. |
| | Never return spills in original containers for re-use. |
| 6.4. Reference to other sections | For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS. |
| SECTION 7: Handling and | storage |
| 7.1. Precautions for safe | Avoid breathing mist/vapours. Provide adequate ventilation. Avoid contact with skin and eyes. |

| 7.1. Precautions for safe handling | Avoid breathing mist/vapours. Provide adequate ventilation. Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices. |
|---|---|
| 7.2. Conditions for safe storage, including any incompatibilities | Store away from incompatible materials. Store in tightly closed container. |
| 7.3. Specific end use(s) | Exhaust putty. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Occupational exposure limits | No exposure limits noted for ingredient(s). |
|--------------------------------------|--|
| Biological limit values | No biological exposure limits noted for the ingredient(s). |
| Recommended monitoring procedures | Follow standard monitoring procedures. |

Derived no effect levels (DNELs)

General Population

| Components | | Value | Assessment factor | Notes |
|-------------------------------------|---|---------------------------|-------------------------------|------------------------|
| Silicic acid, sodium salt (CAS | 1344-09-8) | | | |
| Long-term, Systemic, Der | mal | 0.8 mg/kg | 200 | Repeated dose toxicity |
| Long-term, Systemic, Inh | alation | 1.38 mg/m3 | 50 | Repeated dose toxicity |
| Long-term, Systemic, Ora | al | 0.8 mg/kg | 200 | Repeated dose toxicity |
| <u>Workers</u> | | | | |
| Components | | Value | Assessment factor | Notes |
| Silicic acid, sodium salt (CAS | 1344-09-8) | | | |
| Long-term, Systemic, Der | mal | 1.59 mg/kg | 100 | Repeated dose toxicity |
| Long-term, Systemic, Inh | alation | 5.61 mg/m3 | 25 | Repeated dose toxicity |
| Predicted no effect concentratio | ns (PNECs) | | | |
| Components | | Value | Assessment factor | Notes |
| Silicic acid, sodium salt (CAS | 1344-09-8) | | | |
| Freshwater | | 7.5 mg/l | | |
| Marine water | | 1 mg/l | | |
| STP | | 348 mg/l | 1 | |
| 3.2. Exposure controls | | | | |
| Appropriate engineering controls | Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Observe occupational exposure limits and minimise the risk of exposure. | | | |
| ndividual protection measures, | such as pers | onal protective equipme | ent | |
| General information | Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. | | | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). Eye protection should meet standard EN 166. | | | |
| Skin protection | | | | |
| - Hand protection | Wear suitable gloves tested to EN374. Wear appropriate chemical resistant gloves. Nitrile or neoprene gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier. | | | |
| - Other | Normal work | clothing (long sleeved sh | irts and long pants) is recom | imended. |
| Hylomar Exhaust Repair Putty ERP5 | | | - | SDS Great Brit |

| Respiratory protection | In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P2). |
|---------------------------------|---|
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| Hygiene measures | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. |
| Environmental exposure controls | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Appearance | |
|--|---------------------------------------|
| Physical state | Solid. |
| Form | Putty. |
| Colour | Dark grey. |
| Odour | No characteristic odor. |
| Odour threshold | Not determined. |
| рН | Not determined. |
| Melting point/freezing point | Not determined. |
| Initial boiling point and boiling range | Not determined. |
| Flash point | Not determined. |
| Evaporation rate | Not determined. |
| Flammability (solid, gas) | Will burn if involved in a fire. |
| Upper/lower flammability or exp | losive limits |
| Explosive limit - lower (%) | Not determined. |
| Explosive limit – upper (%) | Not determined. |
| Vapour pressure | Not determined. |
| Vapour density | Not applicable. |
| Relative density | Not determined. |
| Solubility(ies) | |
| Solubility (water) | Insoluble in water. |
| Partition coefficient (n-octanol/water) | Not applicable, product is a mixture. |
| Auto-ignition temperature | Not determined. |
| Decomposition temperature | Not determined. |
| Viscosity | Not determined. |
| Explosive properties | Not explosive. |
| Oxidising properties | Not oxidising. |
| 9.2. Other information | |
| Density | 1.89 (Water = 1) (25 °C) |
| Kinematic viscosity | Not applicable. |

SECTION 10: Stability and reactivity

| 10.1. Reactivity | The product is stable and non reactive under normal conditions of use, storage and transport. |
|---|--|
| 10.2. Chemical stability | Material is stable under normal conditions. |
| 10.3. Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| 10.4. Conditions to avoid | Contact with incompatible materials. Avoid temperatures exceeding the flash point. |
| 10.5. Incompatible materials | Strong oxidising agents. Fluorine. Fluorides. |
| 10.6. Hazardous decomposition products | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Silicon oxides. |

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

| Information on likely routes of exposure | | | |
|--|--|--|--|
| Inhalation | In high concentrations, vapours may be irritating to the respiratory system. | | |
| Skin contact | Causes skin irritation. | | |
| Eye contact | Causes serious eye irritation. | | |
| Ingestion | May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure. | | |
| Symptoms | Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. | | |

11.1. Information on toxicological effects

Acute toxicity

| Components | Species | Test Results | |
|--|---|---|--|
| Silicic acid, sodium salt (CAS 134 | - | 1631 (1630)(3 | |
| Acute | +4-09-0) | | |
| Dermal | | | |
| LD50 | Rat | > 5000 mg/kg, 24 Hours | |
| Inhalation | | | |
| Vapour | | | |
| LC50 | Rat | > 2.06 mg/l, 4 Hours | |
| Oral | | | |
| LD50 | Rat | 2000 - 2500 mg/kg | |
| | | 3400 mg/kg | |
| | | 3200 mg/kg | |
| Skin corrosion/irritation | Causes skin irritation. | | |
| Serious eye damage/eye rritation | Causes serious eye irritatio | | |
| Respiratory sensitisation | Based on available data, tl | classification criteria are not met. | |
| Skin sensitisation | Based on available data, th | classification criteria are not met. | |
| Germ cell mutagenicity | Based on available data, the classification criteria are not met. | | |
| Carcinogenicity | Based on available data, tl | classification criteria are not met. | |
| Reproductive toxicity | Based on available data, tl | classification criteria are not met. | |
| Specific target organ toxicity - single exposure | Based on available data, the classification criteria are not met. | | |
| Specific target organ toxicity - epeated exposure | Based on available data, th | classification criteria are not met. | |
| Silicic acid, sodium salt (CAS | S 1344-09-8) | > 159 mg/kg Result: NOAEL Species: Rat | |
| Aspiration hazard | Due to the physical form o | ne product it is not expected to be an aspiration hazard. | |
| Aixture versus substance nformation | Not available. | | |
| Other information | No other specific acute or | ronic health impact noted. | |
| SECTION 12: Ecological | information | | |
| 12.1. Toxicity | The product is not classifie | as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environment | |
| Components | Species | Test Results | |
| Silicic acid, sodium salt (CAS 134 | • | | |
| Aquatic | | | |
| Acute | | | |
| Crustacea | EC50 Daphnia m | na 1700 mg/l, 48 hours | |
| Fish | LC50 Danio rerio | 1108 mg/l, 96 hours | |
| 12.2. Persistence and degradability | | of inorganic compounds which are not biodegradable. The remainir e expected to be easily biodegradable. | |

| 12.3. Bioaccumulative potential | No data available. |
|--|---|
| Partition coefficient n-octanol/water (log Kow) | Not available. |
| Bioconcentration factor (BCF) | Not available. |
| 12.4. Mobility in soil | The product is insoluble in water. Expected to have low mobility in soil. |
| 12.5. Results of PBT and vPvB assessment | This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. |
| 12.6. Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

SECTION 13: Disposal considerations

| 13.1. Waste treatment methods | |
|-------------------------------|--|
| Residual waste | Do not discharge into rivers, lakes, mountains, etc. because the product may affect the environment. |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. |
| EU waste code | The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. 08 04 09* |
| Disposal methods/information | Do not discharge into drains, water courses or onto the ground. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. |

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

ΙΑΤΑ

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended Not listed.

Not applicable.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Silicic acid, sodium salt (CAS 1344-09-8)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

This product is classified and labelled in accordance with the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

| | ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstract Service. CEN: European Committee for Standardization. EC50: Effective Concentration, 50%. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. LC50: Lethal Concentration, 50%. LD50: Lethal Dose, 50%. MARPOL: International Convention for the Prevention of Pollution from Ships. NOAEL: No observed adverse effect level. PBT: Persistent, bioaccumulative and toxic. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STP: Sewage treatment plant. TWA: Time Weighted Average. vPvB: Very persistent and very bioaccumulative. |
|--|---|
| References | HSDB® - Hazardous Substances Data Bank ECHA CHEM |
| Information on evaluation method leading to the classification of mixture | The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12. |
| Full text of any H-statements not written out in full under Sections 2 to 15 | H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. |
| Training information | Follow training instructions when handling this material. |
| Disclaimer | Hylomar Ltd. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to |

assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.