



Prestone



## SAFETY DATA SHEET Bradex Easy Start

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name	Bradex Easy Start
Product number	BES1A
Internal identification	PA013L
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

#### 1.3. Details of the supplier of the safety data sheet

Supplier A Holts Car Care Product  
Holt Lloyd International Ltd  
Barton Dock Road  
Stretford  
Manchester  
M32 0YQ - England, UK  
+44 (0) 161 866 4800  
FAX +44 (0) 161 866 4854  
www.holtsauto.com

Contact person Contact Email address: info@holtsauto.com

#### 1.4. Emergency telephone number

Emergency telephone UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167

National emergency telephone number <https://poisoncentres.echa.europa.eu/>

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Acute Tox. 4 - H302 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) Xn;R22. F+;R12. R19,R52/53,R66,R67.

#### 2.2. Label elements

## Bradex Easy Start

### Pictogram



### Signal word

Danger

### Hazard statements

H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated  
 H302 Harmful if swallowed.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P102 Keep out of reach of children.  
 P101 If medical advice is needed, have product container or label at hand.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P501 Dispose of contents/ container in accordance with local regulations.

### Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.  
 EUH019 May form explosive peroxides.

### Contains

DIETHYL ETHER, Naphtha (petroleum), hydrotreated light, DI-ISOPROPYL ETHER, ACETONE

### Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P273 Avoid release to the environment.  
 P301+P312 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P330 Rinse mouth.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

DIETHYL ETHER		10-30%
CAS number: 60-29-7	EC number: 200-467-2	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 1 - H224	F+;R12 R19 Xn;R22 R66 R67	
Acute Tox. 4 - H302		
STOT SE 3 - H336		

## Bradex Easy Start

<b>Naphtha (petroleum), hydrotreated light</b>	<b>10-30%</b>
CAS number: 64742-49-0	EC number: 265-151-9
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R65. Xi;R38. F;R11. N;R51/53. R67.
<b>DI-ISOPROPYL ETHER</b>	<b>10-30%</b>
CAS number: 108-20-3	EC number: 203-560-6
<b>Classification</b> Flam. Liq. 2 - H225 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 R19 R66 R67
<b>BUTANE</b>	<b>10-30%</b>
CAS number: 106-97-8	EC number: 203-448-7
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12
<b>ACETONE</b>	<b>5-10%</b>
CAS number: 67-64-1	EC number: 200-662-2
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xi;R36 R66 R67
<b>ISOBUTANE</b>	<b>5-10%</b>
CAS number: 75-28-5	EC number: 200-857-2
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	DO NOT induce vomiting. Get medical attention immediately.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

## Bradex Easy Start

**Eye contact** Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Get medical attention promptly if symptoms occur after washing.

**Inhalation** Vapours may cause headache, fatigue, dizziness and nausea. In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death.

**Ingestion** Due to the physical nature of this material it is unlikely that swallowing will occur.

**Skin contact** Prolonged contact may cause redness, irritation and dry skin.

**Eye contact** Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Not considered to be a significant hazard due to the small quantities used.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## Bradex Easy Start

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### **DIETHYL ETHER**

Long-term exposure limit (8-hour TWA): WEL 100 ppm 310 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 620 mg/m<sup>3</sup>

##### **DI-ISOPROPYL ETHER**

Long-term exposure limit (8-hour TWA): WEL 250 ppm 1060 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 310 ppm 1310 mg/m<sup>3</sup>

##### **BUTANE**

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

##### **ACETONE**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

##### **ISOBUTANE**

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit

### 8.2. Exposure controls

#### Protective equipment



#### **Appropriate engineering controls**

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

#### **Eye/face protection**

No specific eye protection noted, but may be required anyway.

#### **Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

#### **Other skin and body protection**

Wear appropriate clothing to prevent reasonably probable skin contact.

#### **Hygiene measures**

Wash hands after handling.

#### **Respiratory protection**

No specific recommendations.

#### **Environmental exposure controls**

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

## Bradex Easy Start

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Clear liquid. Colourless.
<b>Odour</b>	Organic solvents.
<b>Flash point</b>	-38°C
<b>Auto-ignition temperature</b>	180°C

#### 9.2. Other information

<b>Other information</b>	Not relevant.
--------------------------	---------------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	Vapours may form explosive mixtures with air.
-------------------	---

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures.
------------------	--

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Not determined.
---	-----------------

#### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.
----------------------------	---

#### 10.5. Incompatible materials

<b>Materials to avoid</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
---------------------------	--

#### 10.6. Hazardous decomposition products

<b>Hazardous decomposition products</b>	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ).
---	--

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

<b>Toxicological effects</b>	No data recorded.
------------------------------	-------------------

<b>Other health effects</b>	There is no evidence that the product can cause cancer.
-----------------------------	---

#### Acute toxicity - oral

<b>ATE oral (mg/kg)</b>	1,857.36
-------------------------	----------

<b>Inhalation</b>	Vapours may cause drowsiness and dizziness. Vapours may cause headache, fatigue, dizziness and nausea.
-------------------	--

<b>Ingestion</b>	Harmful if swallowed. Swallowing concentrated chemical may cause severe internal injury.
------------------	--

<b>Skin contact</b>	Irritating to skin. Product has a defatting effect on skin. May cause allergic contact eczema.
---------------------	--

## Bradex Easy Start

**Eye contact** Vapour or spray in the eyes may cause irritation and smarting. Repeated exposure may cause chronic eye irritation.

**Route of entry** Inhalation Skin and/or eye contact

### SECTION 12: Ecological Information

**Ecotoxicity** Dangerous for the environment. May cause long-term adverse effects in the aquatic environment. However, The product is not expected to be toxic to aquatic organisms.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

**Persistence and degradability** The product is expected to be biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** The product does not contain any substances expected to be bioaccumulating.

#### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

#### 12.6. Other adverse effects

**Other adverse effects** The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal methods** Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses.

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

## Bradex Easy Start

### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



### 14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

### 14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.



## Bradex Easy Start

### SECTION 16: Other information

**Revision date** 06/09/2016

**Revision** 6

**Supersedes date** 08/09/2014

**SDS number** 14771

**Risk phrases in full**

- R11 Highly flammable.
- R12 Extremely flammable.
- R19 May form explosive peroxides.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

**Hazard statements in full**

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: may burst if heated
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.