

**RUST REPAIR LIQUID** 

Page: 1

Compilation date: 17/06/2015

**Revision date:** 13/11/2015

Revision No: 2

# Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: RUST REPAIR LIQUID

Product code: 0643,0644,0645

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name: Granville Oil & Chemicals Ltd.

Unit 29 Goldthorpe Industrial Estate

Goldthorpe

Rotherham

South Yorkshire

S63 9BL

United Kingdom

**Tel:** +44 (0)1709 890099 **Fax:** +44 (0)1709 891121

Email: technical@granvilleoil.com

## 1.4. Emergency telephone number

Emergency tel: +44 (0)1709 890099

(office hours only)

### Section 2: Hazards identification

# 2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

## 2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P102: Keep out of reach of children.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

#### **RUST REPAIR LIQUID**

Page: 2

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+312: IF SWALLOWED: Call a POISON CENTER/doctor/ if you feel unwell.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P332+313: If skin irritation occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P405: Store locked up.

P501: Dispose of contents/container to Local authority requirements.

#### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### **Hazardous ingredients:**

ORTHOPHOSPHORIC ACID - REACH registered number(s): 01-2119485924-24

EINECS	CAS	PBT / WEL	CLP Classification	Percent
231-633-2	7664-38-2	-	Skin Corr. 1B: H314	10-30%
PROPAN-2-OL				
200-661-7	67-63-0	-	Flam, Lig. 2: H225: Eve Irrit. 2: H319:	1-10%

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	1-10%
			STOT SE 3: H336	

### 2-BUTOXYETHANOL - REACH registered number(s): 01-2119475108-36

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312;	1-10%
			Acute Tox. 4: H302; Eye Irrit. 2: H319;	
			Skin Irrit. 2: H315	

### COCAMIDOPROPYL BETAINE

-	-	-	Eye Dam. 1: H318; Aquatic Chronic 3:	1-10%
			H412	

### Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Get medical attention if any discomfort

continues.

[cont...]

#### **RUST REPAIR LIQUID**

Page: 3

Ingestion: Wash out mouth with water. Do not induce vomiting. If symptoms persist, consult a

doctor

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

# 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be soreness and redness of the mouth and throat.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

#### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Carbon dioxide.

#### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

# 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Wash the spillage site with large amounts of water.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

#### **RUST REPAIR LIQUID**

Page: 4

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection

### 8.1. Control parameters

### **Hazardous ingredients:**

#### **ORTHOPHOSPHORIC ACID...100%**

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1 mg/m3	2 mg/m3	-	-

#### **PROPAN-2-OL**

	UK	999 mg/m3	1250 mg/m3	-	-
--	----	-----------	------------	---	---

#### 2-BUTOXYETHANOL

UK	25 ppm	maa 05	-	-

### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: PVC gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

## Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Beige

Odour: Barely perceptible odour

Solubility in water: Soluble

Relative density: 1.08-1.11 pH: 1.5

#### 9.2. Other information

Other information: No data available.

#### **RUST REPAIR LIQUID**

Page: 5

### Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

### **Hazardous ingredients:**

# **ORTHOPHOSPHORIC ACID...100%**

ORL	RAT	LD50	1530	mg/kg
-----	-----	------	------	-------

#### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

#### 2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

### Relevant hazards for substance:

	ъ .	Б.
Hazard	Route	Basis
Hazara	110010	Daoio

#### **RUST REPAIR LIQUID**

Page: 6

Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may

cause coughing or wheezing.

### **Section 12: Ecological information**

# 12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: No data available.

#### 12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

### 12.4. Mobility in soil

Mobility: No data available.

### 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

# Section 13: Disposal considerations

### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

**Disposal of packaging:** Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

# **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

# **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

#### **RUST REPAIR LIQUID**

Page: 7

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.