

## Material Safety Data Sheet

### Section 1: Information of Manufacturer

Product name: zinc carbon batteries

Product designation: R03

Nominal Voltage: 1.5V

Chemical system: Zinc/ Manganese Dioxide

Designed for recharge: Yes No√

Company name: [REDACTED]  
[REDACTED]  
[REDACTED]  
[REDACTED]

Tel: [REDACTED]

Fax: [REDACTED]

### Section 2: Hazardous Ingredients / Identity Information

MATERIALS	CAS#	APPROXIMATE PERCENT OF TOTAL WEIGHT (~%)
Manganese Dioxide (MnO <sub>2</sub> )	1313-13-9	23.7
Zinc (Zn)	7440-66-6	35.4
Ammonium chloride (NH <sub>4</sub> Cl) and Zinc chloride (ZnCl <sub>2</sub> ) mixture solution	/	19.8

IMPURITY	CAS#	APPROXIMATE PERCENT OF TOTAL WEIGHT (~%)
Mercury (Hg)	7439-97-6	≤0.0001
Lead (Pb)	7439-92-1	≤0.1000
Cadmium (Cd)	7440-43-9	≤0.0020

### **Section 3 : Physical / Chemical Characteristics**

Form :	N.A.	Specific Gravity (H2O=1)	N.A.
Boiling Point	N.A.	Melting Point	N.A.
Vapor Pressure (mm Hg)	N.A.	Evaporation Rate (Buty 1 Acetate=1)	N.A.
Vapor Density ( AIR=1 )	N.A.	pH	N.A.
Solubility in Water	N.A.	Appearance and Odor	N.A.

### **Section 4: Hazard classification**

N.A.

### **Section 5: Reactivity Data**

Stability	Unstable ( )	Conditions to Avoid
Yes (X)	Stable (X)	

Incompatibility (Materials to Avoid)

Hazardous Decomposition or By products

When heated, battery may emit hazardous vapour of KOH/ NaOH and Hg

Hazardous Reactions	May Occur ( )	Conditions to Avoid
Yes (X)	Will Not Occur (X)	

### **Section 6: Health Hazard Data**

Route(s) of Entry Yes=(X)

Inhalation (N.A.)

Skin(N.A.)

Ingestion (N.A.)

Health Hazard (Acute and Chronic ) / Toxicological in formation

In case of electrolyte leakage, skin will be itchy when contaminated with electrolyte.

In contact with electrolyte can cause severe irritation and chemical burns.

Inhalation of electrolyte vapors may cause irritation of the upper respiratory tract and lungs.

### **Section 7: First Aid Measures**

If electrolyte leakage occurs and makes contact with skin, wash immediately.

If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen minutes, and contact a physician.

If electrolyte vapors are inhaled, provide fresh air and seek medical attention if respiratory irritation develops. Ventilate the contaminated area.

**Section 8: Fire and Explosion Hazard Date**

Flash point (Method Used ): N.A.	Ignition temp.: N.A.
Flammable Limits: N.A.	LEL: N.A.
UEL: N.A.	Extinguishing Media: N.A.
Special Fire Fighting Procedures: N.A.	
Extinguishing Media: Carbon Dioxide, Dry Chemical or Foam extinguishers	

**Unusual Fire and Explosion Hazards**

Do not dispose of battery in fire - may explode.

Do not short - circuit battery - may explode.

**Section 9: Accidental Release or Spillage**

Steps to Be Taken in Case Material is Released or Spilled

Batteries that are leaking should be handled with rubber gloves.

Avoid direct contact with electrolyte.

**Section 10: Handling and Storage**

Safe handling and storage advice

The battery is extremely sensitive to adverse effects of humidity. Be sure to store them in a place that is dry and subject to little temperature change. Do not place near boiler or radiator, nor expose to direct sun light. Do not dispose of the battery in fire. Do not charge the battery. Do not short-circuit the battery. Do not put in backward position. Do not store in disorderly fashion, or allow metal objects to be mixed with stored batteries. Do not disassemble the battery, handling in such manner can cause the battery to explode, leak and injury.

**Section 11: Exposure Controls / Personal Protection**

Occupational Exposure Limits:	LTEP	N.A.	STEP	N.A.
Respiratory Protection(Specify Type)	N.A.			
Ventilation	Local Exhausts	N.A.	Special	N.A.
	Mechanical(general)	N.A.	Other	N.A.
Protection Gloves	N.A.		Eye protection	N.A.
Other Protective Clothing or Equipment	N.A.			
Work /Hygienic Practices	N.A.			

**Section 12: Ecological Information**

N.A.

**Section 13: Disposal Method**

Dispose of batteries according to government regulations

**Section 14: Transportation Information**

Batteries are considered to be "Dry cell" batteries and are unregulated for purposes of transportation by the U.S. Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transport Association (IATA) and International Maritime Dangerous Goods Regulations (IMDG). The only DOT requirement for shipping these batteries is special provision A123 which states: "Batteries, dry are not subject to the requirement of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (For example, by the effective insulation of exposed terminals). As per 59th edition of IATA (2018) requires that batteries being transported by air must be protected from short-circuiting and protected from movement that could lead to short-circuiting.

**Section 15: Regulatory Information**

Special requirement be according to the local regulatory.

**Section 16: Other Information**

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

**Section 17: Measures for fire extinction**

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture. Fire fighters should wear self-contained breathing apparatus.